



**Products**

**Accessories**

**Cable & Pipe Service Location**

**Glass Testing & Measurement**

**Inspection & Detection**

**Ladders**

**Levels**

**Measuring Tools**

[Angle Measurement](#)

[Distance Measuring Wheels](#)

[Environmental Measurement](#)

[Laser Distance Measurement](#)

[Light, Lux & UV Meters](#)

[Moisture Meters](#)

[Packages](#)

[Planimeters](#)

[Scale Rules](#)

[Tapes & Rules](#)

[Telescopic Measuring Rods](#)

[Temperature Measuring](#)

**Protective Clothing**

**Safety Equipment**

**Software**

**Survey Instruments**

**Surveying Accessories**

**Thermal Imaging Cameras**

**Special Offers**

**Product Brands**

## Protimeter Speedy Reagent - Calcium Carbide



This 500g tin of Calcium Reagent is for use with the Speed range of moisture measurement pressure vessels.

The calcium carbide reagent used with the Speedy tester is a hazardous product that must be handled with care by the user and with consideration for the environment.

Users of the Speedy must be familiar with the Speedy Moisture Test Procedure detailed in this manual.

Users must also follow calcium carbide transportation, storage, handling and disposal guidelines in accordance with local regulations and/or the calcium carbide Material Safety Data Sheet (MSDS). Users should be familiar with the hazard identification, first aid measures, fire-fighting measures, accidental release measures, personal protection measures, physical and chemical properties, stability and reactivity, toxicological information, and ecological information as given in the MSDS.